

Data sheet

6ES7331-7HF01-0AB0



Figure similar

SIMATIC S7-300, Analog input SM 331, isolated, 8 AI, resolution 14 bit, 0.052 ms/channel current, Voltage alarm, diagnostics, 1x 20-pole, suitable for isochronous mode Improved bus cycle time for isochronous mode

Supply voltage	
Load voltage L+	
<ul style="list-style-type: none"> • Rated value (DC) • Reverse polarity protection 	24 V Yes
Input current	
from load voltage L+ (without load), max.	50 mA
from backplane bus 5 V DC, max.	100 mA
Power loss	
Power loss, typ.	1.5 W
Analog inputs	
Number of analog inputs	8
permissible input voltage for voltage input (destruction limit), max.	20 V; 20 V DC permanent, 75 V DC for max. 1 s (duty factor 1:20)
permissible input current for current input (destruction limit), max.	40 mA
Input ranges	
<ul style="list-style-type: none"> • Voltage • Current • Thermocouple • Resistance thermometer • Resistance 	Yes Yes No No No
Input ranges (rated values), voltages	
<ul style="list-style-type: none"> • 0 to +10 V • 1 V to 5 V <ul style="list-style-type: none"> — Input resistance (1 V to 5 V) • -1 V to +1 V <ul style="list-style-type: none"> — Input resistance (-1 V to +1 V) • -10 V to +10 V <ul style="list-style-type: none"> — Input resistance (-10 V to +10 V) • -5 V to +5 V <ul style="list-style-type: none"> — Input resistance (-5 V to +5 V) • -500 mV to +500 mV • -80 mV to +80 mV 	No Yes 100 kΩ Yes 10 MΩ Yes 100 kΩ Yes 100 kΩ Yes Yes
Input ranges (rated values), currents	
<ul style="list-style-type: none"> • 0 to 20 mA <ul style="list-style-type: none"> — Input resistance (0 to 20 mA) • -20 mA to +20 mA <ul style="list-style-type: none"> — Input resistance (-20 mA to +20 mA) • 4 mA to 20 mA <ul style="list-style-type: none"> — Input resistance (4 mA to 20 mA) 	Yes 50 Ω Yes 50 Ω Yes 50 Ω

Cable length	• shielded, max.	200 m
Analog value generation for the inputs		
Integration and conversion time/resolution per channel		
• Resolution with overrange (bit including sign), max.	14 bit; Unipolar: 14 bit; bipolar: 13 bit + sign	
• Integration time, parameterizable	Yes	
• Basic conversion time (ms)	52 µs per channel	
• Interference voltage suppression for interference frequency f1 in Hz	none / 400 / 60 / 50 Hz	
Encoder		
Connection of signal encoders		
• for current measurement as 2-wire transducer	Yes	
• for current measurement as 4-wire transducer	Yes	
Errors/accuracies		
Operational error limit in overall temperature range		
• Voltage, relative to input range, (+/-)	0.4 %	
• Current, relative to input range, (+/-)	0.3 %	
Basic error limit (operational limit at 25 °C)		
• Voltage, relative to input range, (+/-)	0.25 %	
• Current, relative to input range, (+/-)	0.2 %	
Interrupts/diagnostics/status information		
Diagnostics function	Yes	
Alarms		
• Diagnostic alarm	Yes; Parameterizable	
• Limit value alarm	Yes; Parameterizable, channels 0 and 2	
Diagnoses		
• Diagnostic information readable	Yes	
Diagnostics indication LED		
• Group error SF (red)	Yes	
Potential separation		
Potential separation analog inputs		
• between the channels	No	
• between the channels and backplane bus	Yes	
• between the channels and the power supply of the electronics	Yes	
Isolation		
Isolation tested with	500 V DC	
connection method		
required front connector	20-pin	
Dimensions		
Width	40 mm	
Height	125 mm	
Depth	117 mm	
Weights		
Weight, approx.	230 g	

last modified:

8/16/2023 