



Figure similar

SIMATIC S7-300, cam controller, FM 352, electronic incl. configuration package on CD

| Supply voltage | |
|---|--|
| Rated value (DC) | 24 V |
| Input current | |
| from load voltage L+ (without load), max. | 200 mA |
| from backplane bus 5 V DC, max. | 100 mA |
| Encoder supply | |
| 5 V encoder supply | |
| • 5 V | Yes |
| • Output current, max. | 300 mA |
| • Cable length, max. | 32 m |
| 24 V encoder supply | |
| • 24 V | Yes |
| • Output current, max. | 300 mA |
| • Cable length, max. | 100 m |
| Power loss | |
| Power loss, typ. | 8.1 W |
| Digital inputs | |
| Number of digital inputs | 4 |
| Functions | Reference point switch, set floating actual value/length measurement, brake release, enable track output no. 3 |
| Input voltage | |
| • Rated value (DC) | 24 V |
| • for signal "0" | -30 to +5 V |
| • for signal "1" | +11 to +30V |
| Input current | |
| • for signal "0", max. (permissible quiescent current) | 2 mA |
| • for signal "1", typ. | 9 mA |
| Digital outputs | |
| Number of digital outputs | 13 |
| Functions | Cam track |
| Short-circuit protection | Yes |
| Output voltage | |
| • Rated value (DC) | 24 V |
| • for signal "1", min. | UP - 0.8 V |
| Output current | |
| • for signal "1" permissible range for 0 to 60 °C, min. | 5 mA; with UPmax |
| • for signal "1" permissible range for 0 to 60 °C, max. | 600 mA; with UPmax |
| • for signal "0" residual current, max. | 0.5 mA |
| Encoder | |

| | |
|--|---|
| Connectable encoders | |
| • Incremental encoder (symmetrical) | Yes |
| • Incremental encoder (asymmetrical) | Yes |
| • Absolute encoder (SSI) | Yes |
| • 2-wire sensor | Yes |
| — permissible quiescent current (2-wire sensor), max. | 2 mA |
| Encoder signals, incremental encoder (symmetrical) | |
| • Trace mark signals | A, notA, B, notB |
| • Zero mark signal | N, notN |
| • Input voltage | 5 V difference signal (phys. RS 422) |
| • Input frequency, max. | 1 MHz |
| Encoder signals, incremental encoder (asymmetrical) | |
| • Trace mark signals | A, B |
| • Zero mark signal | N |
| • Input voltage | 24 V |
| • Input frequency, max. | 50 kHz; 50 kHz for 25 m cable length; 25 kHz for 100 m cable length |
| Encoder signals, absolute encoder (SSI) | |
| • Data signal | DATA, notDATA |
| • Clock signal | CL, notCL |
| • Telegram length, parameterizable | 13 or 25 bit |
| • Clock frequency, max. | 1 MHz |
| • Gray code | Yes |
| • Cable length, shielded, max. | 320 m; at max. 125 kHz |
| Potential separation | |
| Potential separation digital inputs | |
| • Potential separation digital inputs | No |
| Potential separation digital outputs | |
| • Potential separation digital outputs | No |
| Ambient conditions | |
| Ambient temperature during operation | |
| • min. | 0 °C |
| • max. | 60 °C |
| Ambient temperature during storage/transportation | |
| • min. | -40 °C |
| • max. | 70 °C |
| connection method | |
| required front connector | 1x 20-pin |
| Dimensions | |
| Width | 80 mm |
| Height | 125 mm |
| Depth | 120 mm |
| Weights | |
| Weight, approx. | 550 g |

last modified: 8/16/2023 