

product type designation



CP 1613 A2

***** spare part ***** communications processor CP 1613 A2 PCI card (32-bit; 33 MHz/ 66 MHz; 3, 3 V/5 V universal key) for connection to Industrial Ethernet (10/100 Mbit/s) with ITP and RJ 45 connection via HARDNET-IE S7 and S7-Redconnect. operating system support see SIMATIC NETsoftware.

| transfer rate | |
|--|-----------------------------------|
| transfer rate | 10 Mbit/s, 100 Mbit/s |
| interfaces | |
| number of electrical connections | |
| • at the 1st interface / according to Industrial Ethernet | 2 |
| type of electrical connection | |
| • at the 1st interface / according to Industrial Ethernet | RJ45 port / 15-pin ITP connection |
| supply voltage, current consumption, power loss | |
| type of voltage / of the supply voltage | DC |
| supply voltage | |
| • 1 / from backplane bus | 5 V |
| • 2 / from backplane bus | 12 V |
| relative symmetrical tolerance / at DC | |
| • at 5 V | 5 % |
| • at 12 V | 5 % |
| consumed current | |
| • 1 / from backplane bus / at DC / maximum | 0.45 A |
| • 2 / from backplane bus / at DC / maximum | 0.5 A |
| power loss [W] | 4 W |
| ambient conditions | |
| ambient temperature | |
| • during operation | 5 ... 55 °C |
| • during storage | -20 ... +60 °C |
| • during transport | -20 ... +60 °C |
| relative humidity / at 25 °C / without condensation / during operation / maximum | 95 % |
| protection class IP | IP00 |
| design, dimensions and weights | |
| module format | PCI |
| width | 21.6 mm |
| height | 107 mm |
| depth | 167 mm |
| net weight | 140 g |
| product features, product functions, product components / general | |
| number of plug-in cards of same design / plug-in / per PC station | 4 |
| number of units / note | - |
| performance data / open communication | |
| software / for open communication / by means of SEND/RECEIVE / required | Yes, HARDNET-IE S7 (S7-1613) |

| | |
|--|--|
| number of possible connections / for open communication / by means of SEND/RECEIVE / maximum | 120 |
| performance data / S7 communication | |
| software / for S7 communication / required | Yes, HARDNET-IE S7 (S7-1613) |
| number of possible connections / for S7/PG communication / maximum | 120 |
| number of possible connections / for optimized S7 communication / maximum | 40 |
| performance data / multi-protocol mode | |
| number of active connections / with multi-protocol mode | 120 |
| number of configurable connections / per PC station | 207 |
| performance data / PROFINET CBA | |
| software / for PROFINET CBA communication / required | Yes, PN CBA OPC server |
| number of remote connection partners / with PROFINET CBA | 228 |
| number of connections / with PROFINET CBA / total | 10000 |
| product functions / management, configuration, engineering | |
| product function / MIB support | Yes |
| protocol / is supported | |
| • SNMP v1 | Yes |
| • SNMP v3 | No |
| • DCP | Yes |
| • LLDP | No |
| configuration software / required | Included in the scope of delivery of the required software product |
| configuration software / for PROFINET CBA / required | Yes, SIMATIC iMAP |
| identification & maintenance function | |
| • I&M0 - device-specific information | Yes |
| • I&M1 - higher level designation/location designation | Yes |
| • I&M2 - installation date | No |
| • I&M3 - comment | No |
| • I&M4 - signature | No |
| • I&M4 - OEM data | No |
| product functions / redundancy | |
| software / for redundancy function / required | Yes, HARDNET-IE S7-REDCONNECT for communication with SIMATIC S7 H systems |
| product functions / time | |
| product function / SICLOCK support | Yes |
| protocol / is supported / NTP | No |
| standards, specifications, approvals | |
| standard | |
| • for EMC | 2004/108/EC |
| • for safety / from CSA and UL | CAN/CSA C22.2 & UL 60950-1, UL 1950 |
| • for emitted interference | EN 61000-6-3, EN 61000-6-4 |
| • for interference immunity | EN 61000-6-1, EN 61000-6-2 |
| certificate of suitability | |
| • CE marking | Yes |
| • C-Tick | Yes |
| further information / internet links | |
| internet link | |
| • to web page: selection aid TIA Selection Tool | http://www.siemens.com/tia-selection-tool |
| • to website: Industrial communication | http://www.siemens.com/simatic-net |
| • to website: Industry Mall | http://www.siemens.com/industrial-controls/mall |
| • to website: Information and Download Center | http://www.siemens.com/industry/infocenter |
| • to website: Image database | http://automation.siemens.com/bilddb |
| • to website: CAX-Download-Manager | http://www.siemens.com/cax |
| • to website: Industry Online Support | https://support.industry.siemens.com |
| security information | |
| security information | Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection |

concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. (V3.4)

last modified:

11/9/2023 