SIEMENS

Data sheet

6GK5116-0BA00-2AC2



SCALANCE XC116, Unmanaged IE switch, 16x 10/100 Mbit/s RJ45 ports, LED diagnostics, error-signaling contact with set pushbutton, redundant power supply Manual available as a download .

product type designation	SCALANCE XC116	
transfer rate	SCALANCE ACTIO	
transfer rate	10 Mbit/c 100 Mbit/c	
	10 Mbit/s, 100 Mbit/s	
interfaces / for communication / maximum configuration for mod		
number of electrical ports / maximum	16	
interfaces / for communication / integrated		
number of electrical connections		
 for network components or terminal equipment 	16; RJ45	
interfaces / other		
number of electrical connections		
 for signaling contact 	1	
for power supply	1	
type of electrical connection		
 for signaling contact 	2-pole terminal block	
 for power supply 	4-pole terminal block	
signal inputs/outputs		
operating voltage / of the signaling contacts		
at DC / rated value	24 V	
operational current / of the signaling contacts		
• at DC / maximum	0.1 A	
supply voltage, current consumption, power loss		
product component / connection for redundant voltage supply	Yes	
type of voltage / 1 / of the supply voltage	DC	
 supply voltage / 1 / rated value 	24 V	
 power loss [W] / 1 / rated value 	5.4 W	
 consumed current / 1 / at rated supply voltage / maximum 	0.45 A	
 supply voltage / 1 / rated value 	9.6 31.2 V	
 type of electrical connection / 1 / for power supply 	4-pole terminal block	
 product component / 1 / fusing at power supply input 	Yes	
 fuse protection type / 1 / at input for supply voltage 	2.5 A / 125 V	
ambient conditions		
ambient temperature		
during operation	-40 +70 °C	
during storage	-40 +85 °C	
during transport	-40 +85 °C	
relative humidity		
• at 25 °C / without condensation / during operation / maximum	95 %	
protection class IP	IP20	
design, dimensions and weights		

design	compact		
design	compact		
width	120 mm		
height	147 mm		
depth	125 mm		
net weight	0.775 kg		
material / of the enclosure	Polycarbonate (PC-GF10)		
fastening method			
35 mm top hat DIN rail mounting	Yes		
• wall mounting	Yes		
• S7-300 rail mounting	Yes		
S7-1500 rail mounting	Yes		
product features, product functions, product components / general			
number of automatically learnable MAC addresses	2048		
product functions / management, configuration, engineering			
product function			
 multiport mirroring 	No		
• CoS	Yes		
product function / switch-managed	No		
product function			
 is supported / identification link 	Yes; according to IEC 61406-1:2022		
product functions / redundancy			
product function			
 Parallel Redundancy Protocol (PRP)/operation in the PRP-network 	Yes		
 Parallel Redundancy Protocol (PRP)/Redundant Network Access (RNA) 	No		
standards, specifications, approvals			
standard			
 for safety / from CSA and UL 	UL 60950-1, CSA C22.2 No. 60950-1		
for emitted interference	EN 61000-6-4 (Class B)		
reference code			
 according to IEC 81346-2 	KF		
 according to IEC 81346-2:2019 	KFE		
standards, specifications, approvals / CE			
certificate of suitability / CE marking	Yes		
standards, specifications, approvals / hazardous environments			
standard / for hazardous zone	EN 60079-0:2012 + A11:2013, EN60079-15:2010, II 3 G Ex nA IIC T4 Gc,		
	KEMA 07ATEX0145 X, IEC 6079-0:2011, IEC 6079-0-15:2010		
from CSA and UL	UL 1604 and UL 2279-15 (Hazardous Location), Class 1 / Division 2 / Group A, B, C, D / T., Class 1 / Zone 2 / Group IIC / T		
certificate of suitability			
CCC / for hazardous zone according to GB standard	Yes; GB3836.1, GB3836.8		
 CCC / for hazardous zone according to GB standard / as 	Ex nA IIC T4 Gc		
marking			
standards, specifications, approvals / other			
laser protection class	LED Class 1		
certificate of suitability	EN 61000-6-2, EN 61000-6-4		
• C-Tick	Yes		
 KC approval 	Yes		
• E1 approval	No		
• EC Declaration of Conformity EN 61010, IEC 61010-1, UL 61010A-1	Yes		
standards, specifications, approvals / marine classification			
Marine classification association			
 American Bureau of Shipping Europe Ltd. (ABS) 	Yes		
 French marine classification society (BV) 	Yes		
Det Norske Veritas (DNV)	No		
Germanische Lloyd (GL)	No		
• DNV GL	Yes		
 Lloyds Register of Shipping (LRS) 	Yes		
 Polski Rejestr Statkow (PRS) 	Yes		
 Royal Institution of Naval Architects (RINA) 	Yes		

standards, specifications, approvals / Environmental Product	Declaration	standards, specifications, approvals / Environmental Product Declaration					
Environmental Product Declaration	Yes						
 Global Warming Potential [CO2 eq] / total 	441.1 kg	441.1 kg					
Global Warming Potential [CO2 eq] / during	47.67 kg	47.67 kg					
manufacturing	202.02.62						
Global Warming Potential [CO2 eq] / during operation	392.82 kg						
global warming potential [CO2 eq] / after end of life further information / internet links	0.57 Kg	0.57 kg					
	_						
internet link	http://www.sigmons.com/tip.s						
 to web page: selection aid TIA Selection Tool to website: Industrial communication 	http://www.siemens.com/tia-selection-tool http://www.siemens.com/simatic-net						
to website: Industrial communication	https://mall.industry.siemens.com						
to website: Information and Download Center		http://www.siemens.com/industry/infocenter					
to website: Selection guide for cables and connectors	https://sie.ag/2QdlxcP	<u>Su ymnocenter</u>					
to website: Image database		http://automation.siemens.com/bilddb					
to website: CAx-Download-Manager	http://www.siemens.com/cax						
to website: Industry Online Support	https://support.industry.sieme	ns.com					
security information							
security information	Siemens provides products ar	nd solutions with industrial	security functions that				
	the-art industrial security concept. Siemens' products and solutions constitute one element of such a concept. Customers are responsible for preventing unauthorized access to their plants, systems, machines and networks. Such systems, machines and components should only be connected to an enterprise network or the internet if and to the extent such a connection is necessary and only when appropriate security measures (e.g. firewalls and/or network segmentation) are in place. For additional information on industrial security measures that may be implemented, please visit https://www.siemens.com/industrialsecurity. Siemens' products and solutions undergo continuous development to make them more secure. Siemens strongly recommends that product updates are applied as soon as they are available and that the latest product versions are used. Use of product versions that are no longer supported, and failure to apply the latest updates may increase customer's exposure to cyber threats. To stay informed about product updates, subscribe to the Siemens Industrial Security RSS Feed under https://www.siemens.com/cert. (V4.6)						
Approvals / Certificates			For use in hazard-				
General Product Approval		EMC	ous locations				
Manufacturer Declara- tion EG-Konf.			IECEx				
For use in hazardous locations	Marine / Shipping						
EM CCC-	Ex Official Abs	BUREAU VERITAS	Lloyd's Register uis				
Marine / Shipping		other	Environment				
NK / Nippon Kaiji Ky- okai PRS RINA		Manufacturer Declara- tion	<u>Confirmation</u>				
Environment							
Environmental Con- firmations							

last modified:

11/9/2023 🖸