# **SIEMENS**

# **Data sheet**

# 6GK5204-0BA00-2BA3



SCALANCE X204IRT, managed IE IRT switch, 4x 10/100 Mbit/s RJ45 ports, Error signaling contact with set pushbutton, redundant power supply, PROFINET IO device, network management, Redundancy Manager integrated, incl. electron. manual on CD-ROM, C-plug optional.

product type designation	SCALANCE X204IRT
transfer rate	
transfer rate	10 Mbit/s, 100 Mbit/s
interfaces / for communication / integrated	
number of electrical connections	
<ul> <li>for network components or terminal equipment</li> </ul>	4
interfaces / other	
number of electrical connections	
<ul> <li>for signaling contact</li> </ul>	1
<ul><li>for power supply</li></ul>	1
type of electrical connection	
for signaling contact	2-pole terminal block
<ul><li>for power supply</li></ul>	4-pole terminal block
design of the removable storage	
• C-PLUG	Yes
signal inputs/outputs	
operating voltage / of the signaling contacts	
at DC / rated value	24 V
operational current / of the signaling contacts	
• at DC / maximum	0.1 A
supply voltage, current consumption, power loss	
product component / connection for redundant voltage supply	Yes
type of voltage / 1 / of the supply voltage	DC
<ul> <li>supply voltage / 1 / rated value</li> </ul>	24 V
<ul><li>power loss [W] / 1 / rated value</li></ul>	4.8 W
<ul><li>supply voltage / 1 / rated value</li></ul>	18 32 V
<ul><li>consumed current / 1 / maximum</li></ul>	0.2 A
<ul> <li>type of electrical connection / 1 / for power supply</li> </ul>	4-pole terminal block
<ul> <li>product component / 1 / fusing at power supply input</li> </ul>	Yes
<ul> <li>fuse protection type / 1 / at input for supply voltage</li> </ul>	0.6 A / 60 V
ambient conditions	
ambient temperature	
<ul> <li>during operation</li> </ul>	-40 +70 °C
during storage	-40 +70 °C
during transport	-40 +70 °C
relative humidity	
• at 25 °C / without condensation / during operation / maximum	95 %
protection class IP	IP30
design, dimensions and weights	

design	compact	
width	60 mm	
height	125 mm	
	124 mm	
depth		
net weight	0.78 kg	
fastening method	V	
35 mm top hat DIN rail mounting	Yes	
• wall mounting	Yes	
• S7-300 rail mounting	Yes	
S7-1500 rail mounting	No	
product features, product functions, product components / gen		
cascading in the case of a redundant ring / at reconfiguration time of <\~0.3\~s	50	
cascading in cases of star topology	any (depending only on signal propagation time)	
product functions / management, configuration, engineering	any (espending only on eigens propagation and)	
product function		
• CLI	Yes	
web-based management	Yes	
MIB support	Yes	
TRAPs via email	Yes	
• configuration with STEP 7	Yes	
• port mirroring	No	
multiport mirroring	No	
with IRT / PROFINET IO switch	Yes	
PROFINET IO diagnosis	Yes	
PROFINET conformity class	C	
network load class / according to PROFINET	2	
product function / switch-managed	Yes	
protocol / is supported	165	
Telnet	Yes	
HTTP	Yes	
	Yes	
HTTPS     TFTP	Yes	
• IFIF • FTP	Yes	
• BOOTP	No	
DCP     LLDP	Yes	
	Yes Yes	
• SNMP v1		
• SNMP v2	Yes	
SNMP v3  identification 2 maintenance function	Yes	
identification & maintenance function	Von	
18M0 - device-specific information     18M1 - higher level designation designation	Yes	
1&M1 - higher level designation/location designation  product functions I diagnostics	Yes	
product functions / diagnostics		
product function	V	
port diagnostics     Antictics Parket Circs	Yes	
statistics Packet Size	Yes	
statistics packet type	Yes	
error statistics	Yes	
product functions / DHCP		
product function		
DHCP client	Yes	
product functions / redundancy		
product function		
ring redundancy	Yes	
<ul> <li>High Speed Redundancy Protocol (HRP)</li> </ul>	Yes	
<ul> <li>high speed redundancy protocol (HRP) with redundancy</li> </ul>	Yes	
manager	Voc	
<ul> <li>high speed redundancy protocol (HRP) with standby redundancy</li> </ul>	Yes	
protocol / is supported / Media Redundancy Protocol (MRP)	Yes	
P		

product function	
<ul> <li>media redundancy protocol (MRP) with redundancy manager</li> </ul>	Yes
<ul> <li>Parallel Redundancy Protocol (PRP)/operation in the PRP-network</li> </ul>	Yes
<ul> <li>Parallel Redundancy Protocol (PRP)/Redundant Network Access (RNA)</li> </ul>	No
passive listening	Yes
product functions / security	
protocol / is supported	
• SSH	Yes
product functions / time	
product function	
SICLOCK support	Yes
protocol / is supported	
• NTP	No
• SNTP	Yes
standards, specifications, approvals	
standard	
• for FM	FM3611: Class 1, Division 2, Group A, B, C, D / T4, CL.1, Zone 2, GP. IIC, T4, FM16US0205X
• for emitted interference	EN 61000-6-4:2001 (Class A)
for interference immunity	EN 61000-6-4:2001
MTBF	80.58 a
reference code	
• according to IEC 81346-2	KF
• according to IEC 81346-2:2019	KFE
standards, specifications, approvals / CE	
certificate of suitability / CE marking	Yes
standards, specifications, approvals / hazardous environments	
standard / for hazardous zone	EN 60079-0 : 2006, EN 60079-15: 2005, II 3 G Ex nA II T4 KEMA 07 ATEX 0145X
from CSA and UL	ANSI / ISA 12.12.01, CSA C22.2 No. 213-M1987, CL. 1 / Div. 2 / GP. A, B, C, D T4, CL. 1 / Zone 2 / GP. IIC, T4, E240480
certificate of suitability	
CCC / for hazardous zone according to GB standard	Yes; GB3836.1, GB3836.8
<ul> <li>CCC / for hazardous zone according to GB standard / as marking</li> </ul>	Ex nA IIC T4 Gc
for cULus HazLoc / as File Nr.	E240480 (NWHP, NWHP7)
standards, specifications, approvals / other	
certificate of suitability	EN 61000-6-4:2001
C-Tick	Yes
KC approval	Yes
railway application in accordance with EN 50155	No
railway application in accordance with EN 50124-1	No
standards, specifications, approvals / marine classification	
Marine classification association	
American Bureau of Shipping Europe Ltd. (ABS)	Yes
French marine classification society (BV)	Yes
Det Norske Veritas (DNV)	No
Germanische Lloyd (GL)	No
• DNV GL	Yes
<ul> <li>Lloyds Register of Shipping (LRS)</li> </ul>	Yes
Nippon Kaiji Kyokai (NK)	Yes
Polski Rejestr Statkow (PRS)	Yes
Royal Institution of Naval Architects (RINA)	Yes
accessories	
product extension / optional / C-PLUG	Yes
further information / internet links	
internet link	
• to web page: selection aid TIA Selection Tool	http://www.siemens.com/tia-selection-tool
to website: Industrial communication	http://www.siemens.com/simatic-net

• to website: Industry Mall

• to website: Information and Download Center

• to website: Selection guide for cables and connectors

• to website: Image database

• to website: CAx-Download-Manager

• to website: Industry Online Support

https://mall.industry.siemens.com

http://www.siemens.com/industry/infocenter

https://sie.ag/2QdlxcP

http://automation.siemens.com/bilddb

http://www.siemens.com/cax

https://support.industry.siemens.com

#### security information

security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)

### Approvals / Certificates

#### **General Product Approval**

Manufacturer Declaration





Miscellaneous



**Miscellaneous** 

**EMC** 

#### For use in hazardous locations









<u>FM</u>

CCC-Ex



### Marine / Shipping









NK / Nippon Kaiji Kyokai



Marine / Shipping

#### Environment





Confirmation

last modified:

11/9/2023